

LNB PANSAT PK8400

\$3,950.00



El dispositivo de alta ganancia para banda KU de Panarex Modelo PK-8400, compatible con Feeds PANSAT y CHAPARRAL.

LNB Pansat PK-8400

Características:

Mod:	PK-8400
Input Frequency:	11.7 ~ 12.75 GHz
Output Frequency:	950 ~ 2000MHz
L.O. Frequency:	10750 + 2MHz
Noise Temp.(@ + 25°C) :	0.6 to 0.9 dB Max.
Input VSWR : 2.5:	1 Typ
Image Rejection:	40 dBc Min.
Conversion Gain:	55 dB Typ.
Output VSWR:	2 : 1 Typ.
Gain Flatness:	6 dBp-p Max.
Gain Ripple(@per Channel):	+/- 1.0 dB Max.
1dB Gain Compression Point:	+5 dBm Max.
Output Impedanc:	75 Ohms
Leakage(@ Input Port):	-60 dBm Max.
Phase noise	-80 dBc/Hz at 10 kHz -95 dBc/Hz at 100 kHz -110 dBc/Hz at 1 kHz
Power Supply:	+12 to +24V DC
Requires Current:	150 mA Max.
Operating Temperature:	-30°C to +60°C
Storage temperature:	-40°C to +80°C
Relative Humidity:	0% to 95% RH
Input Waveguide flange:	WR-75
IF Output Connector:	F-Type Female
Weight:	190g